# ALL ID BT323A **Bluetooth 2D Barcode Scanner**

## **Features**

- 1. Wireless scanning of 1D & 2D barcodes with Bluetooth
- 2. Scanning speed is more than 300 scans per second
- 3. Fast and easy to scan from paper, print and screen
- 4. Easy to connect to various devices with one key only
- 5. Designed to withstand 1.5m drops
- 6. Large capacity battery allows more than 8 hours of continuous scanning and 7 days of standby

# **Specifications**

#### Scan Performance:

• Scan Mode: Automatic / handheld

32 bit

16 MB

256 gray levels

- Processor type:
- Memory:
- Alarm Mode:
- Resolution:
- Scan Angle:

Singapore (HQ)

+65-6778-0075

All ID Asia Pte Ltd

www.allid.com.sg

enquiry@allid.com.sg

Scan depth of field:

45° (horizontal); 30° (vertical) 5 mil (Code 39) 90~120mm 13 mil (UPC/EAN) 30~305mm 20 mil (Code 39) 30~450mm PDF417 (10mil) 50~225mm Datamatrix (10mil) 52~240mm

Red light alarm, Buzzer alarm

640 (horizontal) x 480 (vertical),

• Barcode Type: Australian Post, Aztec, BPO, Canada Post, Codabar, Codablock, Code 11, Code 39, Code 93, Code 128/EAN128, DataMatrix, Dutch Post, EAN.UCC Composite, Interleaved 2 of 5, Japan Post, Matrix 2 of 5, MaxiCode, MicroPDF417, MSI Code, PDF417, Planet, Plessey Code, Postnet, QR code, RSS, Standard 2 of 5, Telepen, TLC 39, UPC/EAN

DC 5V ± 5%

### **Electrical:**

- Voltage:
- Operating Power:
- Interfaces:
- Bluetooth Coverage:
- Light Level:

#### **Environmental:**

- Operating Temp:
- Storage Temp:
- Humidity:
- Drop:
- IP Rating:

#### **Reliability:**

- High Temp:
- Low Temp:
- Cycle Time:
- Cycles:
- Mechanical Shock:

#### **Physical:**

- Weight:
- Color:
- Material:
- Accessories:

• Dimensions (LxWxH): 170mm × 100mm × 75mm 150g (without cable) Scanner, manual, USB cable,

30 minutes for low temp.

2000G, 0.7ms, 3 axes

24 cycles

Product features, specifications and appearances are subject to change without notice. Copyright © 2020 All rights reserved. This product is manufactured, distributed, and sold by All ID Asia.



#### Philippines All ID Philippines +632-224-2042 enquiry@allid.com.ph www.allid.com.ph

Malaysia All ID Asia Sdn Bhd +603-8075-1888 enquiry@allid.com.my www.allid.com.my

#### Indonesia

PT All ID Indonesia +62 21-4517-330 enquiry@allid.co.id www.allid.co.id

Myanmar All ID Myanmar +951-652265

enquiry@allid.com.mm

www.allid.com.mm

Black ABS + EVA 2.4G dongle

300mA (operating) Bluetooth 4.0, 2.4G, USB 30m (in vacant space) Visible Red light 630+10nm -20°C ~ 60°C -30°C ~ 70°C

60mA (working); 40mA (standby);

5% to 95% (Non-condensing) Designed to withstand 1.5m drops IP54

60°C (140°F) -20°C (-4°F) 30 minutes for high temp.,